



# 32-Channel 1U 16 PoE AcuSense 4K Network Video Recorder

DS-7732NXI-I4/16P/S

- H.265+/H.265/H.264+/H.264 video formats
- Intelligent deep learning algorithm
- Up to 16/32-ch IP camera inputs
- Up to 16-ch 1080p decoding capability
- Up to 160/256 Mbps incoming bandwidth

Full Channel  
IP Camera  
Connection

The 32-Channel NVR uses H.265+ compression effectively reduces the storage space by up to 75%. What's more, it utilises TLS encryption technology which provides more secure stream transmission service.

Video output includes independent HDMI and VGA outputs, with HDMI resolution up to 4K.

Features include smart search for the selected area in the video, and smart playback to improve the playback efficiency



Great in  
Low Light



Deep Learning  
Algorithm



Efficient  
Compression



Power over  
Ethernet



TLS  
Encryption

## Features

Features	Connections
Video Output	<p><b>HDMI1 output:</b> 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI1/VGA simultaneous output</p> <p><b>HDMI2 output:</b> 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI2/VGA independent output</p> <p><b>VGA output:</b> 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz, HDMI1/VGA simultaneous output</p>
Audio	<p><b>Output:</b> 1-ch, RCA (Linear, 1 KΩ)</p> <p><b>Two-way input:</b> 1-ch, RCA (2.0 Vp-p, 1 KΩ)</p>
Interface	<p><b>Serial Port:</b> RS-485 (half-duplex), RS-232, Keyboard</p> <p><b>SATA:</b> 4 SATA interfaces supporting hot-plug, 10 TB capacity for each disk</p> <p><b>eSATA:</b> 1 eSATA interface</p>
Dimensions & Weight	<p>445 × 400 × 75 mm (17.5" × 15.7" × 3.0")</p> <p>≤ 7 kg (15.4 lb)</p>