PRODUCT COMPARISON

Poindus PT60 vs PT61

Two compact, all-in-one EPOS terminals built on the same fanless platform. The main difference is the screen: widescreen Full HD or the classic 4:3 shape.



PT60

WIDESCREEN

15.6" Full HD 16:9 touchscreen, with an optional 11.6" customer display.

15.6"	1920 x 1080	380mm
Screen	Resolution	Width



PT61

CLASSIC 4:3

15" 4:3 touchscreen, with an optional 9.7" customer display.

15"	1024 x 768	348mm
Screen	Resolution	Width

Where they differ

Feature	PT60	PT61
Screen size	15.6"	15"
Aspect ratio	16:9 widescreen	4:3 standard
Resolution	1920 x 1080 (Full HD)	1024 x 768
Brightness	300 nits	350 nits
Second display option	11.6" 1366 x 768, with or without touch	9.7" 1024 x 768, non-touch
Made to order	PCAP touch second display, RFID or 2D barcode reader	Not listed by Poindus
Size (W x H x D)	380 x 336 x 212mm	348 x 340 x 212mm
Screen panel depth	44mm	49mm
Weight (net / gross)	6.6kg / 7.2kg	6.7kg / 7.4kg

Which one is right for you?

Choose the PT60

For a modern widescreen layout. The Full HD screen shows more at once, and the larger 11.6" customer display can be specified with touch.

Choose the PT61

For the classic 4:3 screen shape or a tighter counter. It is 32mm narrower, a little brighter at 350 nits and pairs with a 9.7" customer display.

This specification sheet has been prepared for guidance only. While every effort has been made to ensure the information is accurate, errors and omissions may occur. CCR Systems accepts no liability for inaccuracies, missing information or changes to product specifications, availability or compatibility. All details should be confirmed before purchase, installation or implementation.

POINDUS PT60 VS PT61

Full specification comparison

Highlighted rows show where the two models differ. Single values apply to both.

Specification	PT60	PT61
SYSTEM & SOFTWARE		
Processor	Intel® Celeron® J6412 (Elkhart Lake), up to 2.6GHz	
Memory	8GB DDR4 (1 x SO-DIMM), up to 16GB	
Storage	128GB mSATA SSD	
Security	Intel® firmware TPM 2.0	
Expansion	1 x mini-PCIe (Wi-Fi/Bluetooth on request)	
Operating system	Windows 10 / 11 (64-bit), Linux	
Certification	CE / FCC	
DISPLAY		
Screen size	**15.6"**	**15"**
Aspect ratio	**16:9 widescreen**	**4:3 standard**
Resolution	**1920 x 1080 (Full HD)**	**1024 x 768**
Brightness	**300 nits, LED backlight**	**350 nits, LED backlight**
Touch & front panel	PCAP multi-touch, IP54 spill-proof front panel	
CONNECTIVITY & POWER		
Ports	2 x USB 3.0, 4 x USB 2.0 (2 on side), Gigabit LAN, 2 x RS-232 (DB9), VGA, RJ11 cash drawer, mic-in / line-out jack, DC-in	
Audio	2 x 2W speakers	
Power	12V DC, 5A (60W adaptor)	
BUILD & ENVIRONMENT		
Construction	Die-cast aluminium and plastic, technology black; fanless	
Size (W x H x D)	**380 x 336 x 212mm**	**348 x 340 x 212mm**
Screen panel depth	**44mm**	**49mm**
Weight (net / gross)	**6.6kg / 7.2kg**	**6.7kg / 7.4kg**
Environment	Operating 0°C to 40°C; storage -20°C to 60°C; 10% to 90% RH, non-condensing	
OPTIONS & ACCESSORIES		
Card readers	3-track MSR, iButton, MSR + RFID + iButton, MSR + RFID + fingerprint	
Second display	**11.6" 1366 x 768, with or without touch**	**9.7" 1024 x 768, non-touch**
Customer pole display	2 x 20 VFD (USB)	
Made to order	**PCAP touch second display, RFID or 2D barcode reader**	**Not listed by Poindus**

Not sure which suits your venue? Call **0151 644 8296** or email **contact@ccrsystems.co.uk**

This specification sheet has been prepared for guidance only. While every effort has been made to ensure the information is accurate, errors and omissions may occur. CCR Systems accepts no liability for inaccuracies, missing information or changes to product specifications, availability or compatibility. All details should be confirmed before purchase, installation or implementation.